



General

Lloyds Register of Shipping Class \times 100A1 ballastable barge.

Dimensions

Length extreme	91.72 m
Breadth extreme	30.76 m
Depth extreme	7.65 m
Summer draft extreme	6.16 m
Light draft	0.96 m
Length moulded	91.44 m
Breadth moulded	30.48 m
Depth moulded	7.62 m
Deadweight summer draft	13980 tonnes
Lightweight	2262 tonnes
Deck load maximum	15 tonnes/m ²

Anchor winch

Declutchable and lockable drum, without grooves, suitable for 610 m of 40 mm anchor wire. Hydraulically operated from diesel engine/ballast pump unit with 2 manually operated clutches in system.

Capacity	24 tonnes - 12.5 m/min
	10 tonnes - 25 m/min
	5 tonnes - 60 m/min
Brake holding	45 tonnes

Hand winch

Ten tonnes winch suitable for 47 m of 20 mm recovery wire attached to delta plate.

Anchor equipment

Two stockless type, complete with crown shackle and each weighing 5340 kg, built by Byers.

SMIT Transport Europe

P.O. Box 59052
3008 PB Rotterdam
The Netherlands

Tel + 31 10 454 99 11
Fax + 31 10 411 50 95
transport.europe@smit.com
www.smit.com

